



# Specifications

## Ripper teeth

### Rippers

All rippers are constructed using a 400HB material for the main shank and are fitted with a replace-able tip.  
 1 to 37 ton rippers are fitted with standard cat style tips, 38 ton and above are fitted with the MTG ripmet system including front shroud protection



| Machine wt.     | Part No. | Shank Depth | Shank | Tip type  |
|-----------------|----------|-------------|-------|-----------|
| 1 to 2 ton      | R10      | 300mm       | 25mm  | Cat 428   |
| 2 to 4 ton      | R20      | 500mm       | 30mm  | Cat 428   |
| 4 to 6 ton      | R40      | 600mm       | 40mm  | Cat 205   |
| backhoe loaders | R60      | 600mm       | 40mm  | Cat 205   |
| 6 to 10 ton     | R90`     | 750mm       | 50mm  | Cat 215   |
| 11 to 15 ton    | R130     | 750mm       | 50mm  | Cat 225   |
| 16 to 19 ton    | R160     | 750mm       | 60mm  | Cat 225   |
| 20 to 27 ton    | R200     | 900mm       | 60mm  | Cat 235   |
| 28 to 37 ton    | R280     | 950mm       | 80mm  | Cat 245   |
| 38 to 48 ton    | R380     | 1000mm      | 100mm | Ripmet 45 |
| 49 to 60 ton    | R500     | 1100mm      | 100mm | Ripmet 50 |

Capacities are in cubic metres SAE heaped.